



IRIS-L-P LED Pendant Pendant 600mm diameter 6800Lm

LED translucent Pendant IRIS-L-P-6800-840 DA

Design: The IRIS-LED is made of highly transparent plastic. Three specially developed LED ring segment modules for the direct and indirect lighting component, fitted with mid-power LEDs and closed by a highly transparent plastic lens with microprism structure create a unique lighting effect reticent of the human iris. Available light colours are 830 (3000 K) and 840 (4000 K).. The patented pendant solution featuring a three-way split power supply integrated in the pendant cables lends the perfect embodiment to this ring-shaped luminaire. The filigree pendant fixture retreats into the background, leaving only the transparent luminaire body on view. Optical accentuation possible by inserting a separately available colour inlay film for the side edge. The IRIS-P-LED pendant-mounted luminaire is DALI dimmable.

Lamps		Power supply	Product code	
LED		Integral DALI	IRIS-L-P-6800-840 DA	
Luminaire Luminous Flux (Lm) Initial		Luminaire output (W)	Luminaire efficiency (LOR)	Luminous colour
6800Lm		47w	84.3%	4000K
Luminaire Luminous Flux (Lm) Exit		Light distribution Direct / indirect		
5730Lm		44 / 56		
L	B	H		
600 mm	100mm	50 mm		

Dimensions (mm)		Weight (kg)
600 x 100 x 100		6.8kg

