



## Myral Myral ...-S

### MYRAL 1500-840-S

Downlighter for ceiling mounting with high-performance COB LED consisting of a luminaire and driver box. Secondary reflector coated for targeted optical control with a beam angle of 23° (spot). Recess mount housing designed in die-cast aluminium, chemically burnished with high-gloss finish. Tool-free ceiling installation using side clips (ceiling thickness 1-15 mm). The clips are equipped with additional PVC caps to protect the aluminium reflector from plastic deformation caused by falling clips.



LED-COB module in light colour 830 or light colour 840.

Luminaire control gear located in an external driver box. Minimum spacing between luminaire and driver box: 100 mm (see mounting instructions).

Protection rating IP20, protection class I.

Lamps	Ballast	Prod. code
1xLED-M 9 W	LED Driver	SPG0320173

Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [lm/W]
1466	10	146



Dimens. [mm]							Weight [kg]		Photometric data		
L1	B1	H	HE	D	DE min	DE max			Longitudinal UGR	TransverseUGR	LOR
200	70	93	110	120	105	110	0,6		22.9	22.9	99.7 %

### EEC A++ - A

Energy efficiency class scale A++ - E

**Myral**  
**Myral ...-S**