



Myral Myral ...-F

MYRAL 3500-830-F

Downlighter for ceiling mounting with high-performance COB LED consisting of reflector housing and driver box. Secondary reflector coated for targeted optical control with a beam angle of 49° (flood). Recess mount housing designed in die-cast aluminium, chemically burnished with high-gloss finish. Tool-free ceiling installation using side clips (ceiling thickness 1-15 mm). The clips are equipped with additional PVC caps to protect the aluminium reflector from plastic deformation caused by falling clips.



LED-COB module in light colour 830 or light colour 840.

Luminaire control gear located in an external driver box. Minimum spacing between luminaire and driver box: 100 mm (see mounting instructions).

Protection rating IP20, protection class I.

Lamps	Ballast	Prod. code
1xLED-M 24 W	LED Driver	SPG0320186

Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [lm/W]
3217	29	110



Dimens. [mm]							Weight [kg]		Photometric data		
L1	B1	H	HE	D	DE min	DE max			Longitudinal UGR	TransverseUGR	LOR
215	70	93	110	120	105	110	0,6		26.7	26.8	99.9 %

EEC A++ - A

Energy efficiency class scale A++ - E

Myral
Myral ...-F