

Similar photo

Orto ORTO-T ... MR-SEN

ORTO-T 9500-840 MR-SEN

Tablelamp with direct-indirect beam, luminaire head in extruded aluminium, arranged longitudinally to the stand with precision 90° die-cast component, white (similar to RAL9016), powder-coated.

Pre-fitted cell-shaped louvre MR in vapour-coated matte polycarbonate for optical control of direct light distribution. Optical controllers indirect through cover, clear panel.

Mounted on table using clamp stand; clamp width: 15 mm to 40 mm.

Black mains cable with Schuko plug, 3 m in length. Touchpanel for switching and dimming installed in the stand and integrated USB charging station.

Model with sensor for movement-dependent switching and daylight-dependent dimming.

Mid-power LED modules for maximum lighting efficiency.

Colour rendering in index Ra > 80, colour temperature 4000 Kelvin (-840).

Protection class I, protection rating IP20.

Non-standard designs with smooth, polished powder coating, only available in combination with matte brushed nickel or polished chrome corner connector, end cap and stand adapter.

Lamps


1xLED 33 W / 1xLED 40 W

Ballast

LED Driver DALI

Prod. code

SPG0630030AH



Dimens. [mm]			Weight				
L	B	H	[kg]				
1400	62	1460	7,3				

EEC A++ - A

Energy efficiency class scale A++ - E

Orto
ORTO-T ... MR-SEN