## Spectral®





## Pergament Round recessed spot L Pergament large

## EINBAUSTRAHLER-L/26-42 P

Round recessed ceiling downlighter with bayonet fixture of the cover ring in UV stabilised polycarbonate. Inserted in the housing is the facetted parabolic reflector in super-purity specular anodised aluminium. Lamp positioned horizontally. Suspended in the cover ring is an acrylic glass cylinder with polished clear outer sides. Underneath painted matt, scratchproof and insensitive to fingerprints. Toolless ceiling mounting using spring clips, for maximum ceiling thickness of 40 mm. Cover ring standard colour white, optionally separately available in other colours. The external housing accommodates all electrical components, connector block, cable strain relief and connecting cable with lamp holder block. Gear tray in galvanised steel, cover made of thermally resistant plastic. Suitable for separate 3-phase through wiring. Recessed ceiling luminaire with heat-resistant wiring. Protection rating IP 20, safety class I. Colour: similar to RAL 9016 white silk matt

Lamps	Ballast	Socket	Prod. code	Ballast class EEI:
1xTC-TEL 26/32/42 W	Electronic ballast MW	GX24q-3/4	SPE0320771//660	A2





Dimens. [mm]				Weight	Weight Photometric data				
					[kg]		Longitudinal UGR	TransverseUGR	LOR
30	155	275	262	265	1,2		23.7	23.2	43.9 %

## **Spectral**<sup>®</sup>

Pergament Round recessed spot L Pergament large

