



Pergament Square LED recessed ceiling luminaire small

Design

C. Meyer, M. Kocks, P. H. Neuhorst

PERGA-QE 345/2600/840 SI

Square luminaire element comprising an acrylic glass block with transparent superpolished exterior. Underneath painted matt to reduce glare. Luminaire element integrated in a square powder coated steel frame designed for snap fixture into the recessed powder-coated steel ceiling housing. Recessed housing includes clamps with adjustable clamping thickness from 38 to 69 mm for fixture in the ceiling cut-out.. Recessed ceiling housing accommodates the electrical components and electronic ballast. The LED module is formed as a square LED flat board and can be removed for installation or exchange using a fold-out LED carrier. Plug-in electrical connection of the LED flat board. Luminaire with heat-resistant wiring. Homogenous illumination of the light surface. Suitable for ceiling or wall mounting. Light colours 830 or 840. Also in a dimmable version.


Protection rating IP20, safety class I.

Colour:

Metal body – similar to RAL 9016 white silk matt

Frame – white (WS), silver (SI), black (AQ)

Lamps	Ballast	Prod. code
1xLED-M 15 W	LED Driver	SPP0000157



Dimens. [mm]			Weight [kg]				
345	345	162	-				

Pergament
Square LED recessed ceiling luminaire
small

