



Norea Square LED recessed ceiling luminaire medium

Design
P. H. Neuhorst

NOREA-QE 455/5200/840 OS

Square luminaire element with an opal acrylic panel in a natural anodised aluminium profile frame surround. The luminaire is mounted using a fixing kit for fixture in the ceiling cut-out. The fixing kit is for different ceiling thicknesses. The profile frame is suspended in the powder-coated recessed ceiling housing using tension springs. The frame is removed using suction cups. The LED module is formed as a square LED flat board and screwed to the luminaire element. For connection of the luminaire this can be hinged down and fastened with screws at an oblong hole in the recessed ceiling housing. The metal body coated ceiling housing accommodates the electrical components and the electronic ballast. Luminaire with heat-resistant wiring. Homogenous illumination of the light surface. Also in a dimmable version.

Protection rating IP20, safety class I.



Colour:

Housing - similar to RAL 9016 white silk matt;

Frame - natural anodised

Lamps	Ballast	Prod. code
4xLED-M 8 W	LED Driver	SPT0000122

Luminaire luminous flux [lm]	Luminaire output [W]	Luminaire efficiency [lm/W]
3162	39	81



Dims. [mm]						Weight [kg]	Photometric data		
455	455	131				-	Longitudinal UGR	Transverse UGR	LOR
455	455	131				-	22.7	22.1	60.8 %

Norea
Square LED recessed ceiling luminaire
medium

